

Automatic Machine Control System Benefits

- Increase machine productivity and accuracy
- Simplify your grading and increase operator efficiencies
- Reduce labor and wasted downtime waiting for grade checks
- Save material with improved accuracy

Automated Machine Control Systems



Affordable Automatic Blade Control Systems for Site Preparation

Spectra Precision® Laser Automatic Machine Control Systems take grade control to the next level. These systems are designed with the cost-conscious owner / operator and contractor in mind, delivering high-priced performance in affordable packaging. Automatically controlling the blade improves grading operations with increased accuracy and higher profits.

The operator can optimize machine time, effectiveness, and efficiency.

Extremely rugged and highly flexible, machine control systems can be used on a wide range of machines. For even greater productivity, dozers may be upgraded from lift to lift and tilt control.

Used on:

- Skid Steer Blade Attachments
- Levelers
- Kilvers
- Box Blades
- Dozers





Spectra Precision Laser Control Boxes for Affordable Automatic Blade Control

CB30 Dual Control Box

Features and Benefits

- Simultaneous, automatic control of lift and tilt of blade or attachment for less passes required to grade saving time, material, and fuel
- Highly featured to fit multiple machine and application types and priced for quick return on investment
- Super-bright LEDs provide easy-to-see elevation indication in any light for setup and operation

Used on compact machines, including

- Skid-steer loaders with attachments such as 6-way dozer blade, grader blade, box blade, loader bucket for automatic control requiring lift or lift and tilt control
- Small dozer with lift or lift and tilt automatic control
- Small graders for lift and tilt control

Applications

- Building pads
- Sports fields
- House pads



Tough, Affordable Spectra Precision Laser Grade Display Receivers

LR30 for General Excavating

Use on dozers, backhoes, excavators and trenchers. Used with the CB20 Single Control Box



LR50 for Excavating and Grading

Features built-in blade tilt and excavator boom plumb indicator. Used with the CB25 and CB30 Control Boxes



LR60 for Excavating

Features built-in excavator boom plumb and angle compensation indicator. Used with CB25 and CB30 Control Boxes





CB25 Single Control Box



Features and Benefits

- Automatic lift control lets you get to grade faster with less rework and more material savings
- Proportional valve control provides smooth blade response through quick corrections making more consistent and accurate finish grade
- Super-bright grade LEDs and easy-to-see display provide highly visible elevation indication and system status in any light for setup and operation
- On/off automatic/manual switches are easy to set up and use

Used on small and large dozers, and compact machines

- Skid-steer loaders with attachments such as dozer blade, grade blade, box blade, loader bucket for automatic control requiring lift control
- Small dozer with lift and automatic lift control using PT proportional current, proportional voltage

CB20 Single Control Box



Features and Benefits

- Automatic lift control lets you get to grade faster with less rework and more material savings
- Proportional Time (PT) valve control offers economical automatic control
- Super-bright grade LEDs and easy-to-see display provide highly visible elevation indication and system status in any light for setup and operation
- On/off automatic/manual switches are easy to set up and use

Used on compact machines

- Skid-steer loaders with attachments such as dozer blade, grade blade, box blade, loader bucket for automatic control requiring lift control
- Small dozer for lift and automatic lift control using PT output

Spectra Precision Laser Receiver Mast

Manually adjusted telescopic mast mounts to the blade for receiver setup and adjustment.



Specifications	CB30	CB25	CB20
Single Auto Control	Yes	Yes	Yes
Dual Auto Control	Yes	No	No
Slope Control	Yes	No	No
Elevation Coupling	Yes	No	No
On-grade LEDs	Green	Green	Green
High/Low LEDs	Red	Red	Red
Valve Compatibility	Proportional Time (On/Off), Proportional Current, and Proportional Voltage	Proportional Time (On/Off), Proportional Current, and Proportional Voltage	Proportional Time only



Spectra Precision Laser Rugged Grade Laser Transmitters Built for the Job Site

For General Construction and Larger Commercial Sites

For Residential and Smaller Commercial Sites



GL412 Single Grade Laser

Powerful, easy-to-use, single slope grade laser with radio remote

Applications

- Site preparation
- General construction
- Pipe-laying



GL422 Dual Grade Laser

Accurate, multipurpose horizontal, vertical and dual slope grade laser with radio remote

Applications

- Cut and fill
- Excavation
- Elevation and slope control
- Grade/elevation control



GL710 Single Grade Laser

Easy-to-use, single slope grade laser accurate to 900 meters (3,000 feet)

Applications

- Excavating
- Trenching
- Pipe laying
- General construction



GL720 Dual Grade Laser

Economical, high-accuracy dual slope grade laser

Applications

- Excavating
- Trenching
- Pipe laying
- General construction

Specifications	GL412	GL422	GL710	GL720
Level Accuracy	10 arc seconds 1.5 mm @ 30 m (1/16" @ 100 ft)		8 arc seconds 1.2 mm @ 30 m (<1/16" @ 100 ft)	
Grade Range	-10 to +15% Single Axis	-10 to +15% Dual Axes	-10 to +10% Single Axis	-10 to +10% (X Axis) -0.500 to +25% (Y Axis)
Grade Resolution	0.001% up to 9.999%	0.01% at higher grades	0.001% up to 9.999%	0.01% at higher grades
Operating Diameter	600 m / 1950 ft		900 m / 3000 ft	
Laser Type / Classification	3 mW 650 nm, Class 2		<5 mW 635 nm, Class 3A/3R	
Rotation Speed	300, 600 rpm		300, 600, 900 rpm	
Battery Life	55 hrs		30 hrs NiMh	
Mounting Thread	5/8 x 11		5/8 x 11	
Operating Temperature	-20° to +50°C (-4° to +122°F)		-20° to +50°C (-4° to +122°F)	
Dimensions	21L x 18W x 20H cm (8.3L x 7.1W x 7.9H in)		19.7L x 25.4W x 29.8H cm (7.75L x 10.0W x 11.75H in)	
Weight	3.1 kg (6.8 lb)		8.5 kg (18.8 lb)	
Remote Control	Full 2-way communication, operation and transmitter security lock		N/A	N/A
Remote Operating Range	100 m (330 ft) radius		N/A	N/A
Remote Battery Life (2 x AA Alkaline)	130 hrs continuous, 1 year under normal use		N/A	N/A



YOUR LOCAL SPECTRA PRECISION LASER REPRESENTATIVE

NORTH AMERICA

Trimble
5475 Kellenburger Road • Dayton, Ohio 45424 • U.S.A.
800-538-7800 (Toll Free)
+1-937-245-5154 Phone • +1-937-233-9441 Fax

EUROPE

Trimble GmbH
Am Prime Parc 11 • 65479 Raunheim • Germany
+49-6142-2100-0 Phone • +49-6142-2100-550 Fax

ASIA-PACIFIC

Trimble Singapore
80 Marine Parade Road • 22-06, Parkway Parade
Singapore 449269
+65-6-325-5668 Phone • +65-6-348-2232 Fax

www.trimble.com